



SOFTWARE DEFINED RADIO

Mobile *COMP@N*


Radio Communications
of the Future



VERSATILE



FLEXIBLE



**CUSTOMIZED TO MISSION
REQUIREMENTS**

Wide range of functionalities:

- Basic e.g. voice transmissions broadcast
- Complex e.g. MANET radio / all available functions

Within the family of COMP@N radios it is possible to choose between different waveforms (WF) and range of supported frequencies.

Handheld COMP@N radios can be connected to the vehicle adapter and power amplifier to create mobile or stationary set.

Mobile adapter is a device which enables the use of COMP@N handheld radio in vehicles (e.g. light tanks, transporter vehicles). This set provides a secure attachment and a possibility for easy removing of the radio, without outages. After installing the radio in the adapter, it is being automatically switched to work with vehicular data communications system and power amplifier (if such is installed). In such set, a radio is powered via an adapter with the onboard network of the vehicle, while ensuring the charging of its battery from vehicular power supply. The adapter also provides an access to interfaces of the radio through a dedicated connectors, enabling further integration with on-board systems.

Mobile set, which consists of handheld COMP@N radio mounted in vehicular adapter, can be extended with power amplifier. It allows to work with maximum power 50 W, which significantly increase radio range. The amplifier is powered from the vehicular power supply and is designed for all the COMP@N family radios.

The basic parameters of the amplifier

frequency range	30-520 MHz
input voltage	17÷33 V
maximum output power	50 W
dimensions	270 x 180 x 187 mm

The amplifier and adapter can be installed in the vehicle either as a separately mounted devices (e.g. spaced apart to several meters), and as one integrated set.

General specification of the COMP@N platform

FM/AM fixed frequency	modulations	FM, AM	
	transmission modes	F3E, A3E	
	channel	FM: 25 kHz	
		AM: 8.33 kHz, 25 kHz	
	Squelch		
	Nº of channels	1000	
	Scan		
	FCS (free channels search)		
	General	a large color display	
		auto backlight intensity regulation	
menu			
double PTT button			
backlit keyboard			
Emergency Clear button			
build-in GPS receiver			
dimensions (with amplifier & adapter)		270 x 180 x 277 mm	
weight		~ 15 kg	
RF		frequency range	30 ÷ 520 MHz
	output power	up to 50 W	
	suppression of harmonics: > 50 dBc		
	frequency stability: ± 1 ppm		
	sensitivity: - 116 dBm (SINAD 20 dB)		
	adjacent channel selectivity ≥ 50 dB		
Interfaces	Audio / PTT		
	RS232		
	Ethernet 10/100		
	USB		
	Side Connector (to work with COMP@N accesories)		
	Enviromental parameters	operational temperature	-32°C ÷ +55°C
MIL-STD-810G			
EMC MIL-STD-461F			

COMP@N H07 Waveforms

DV operating modes FH (Frequency Hopping): 100 hop/s

FF (Fixed Frequency)

digital voice transmission

channel 25 kHz

security (AES-256 based) TRANSEC

COMSEC

pre-defined profiles with set of mission parameters (radio data, encryption keys)

RSD channel 25 kHz

capability to enter data via Ethernet or serial port

capability to transmit GPS reports

modulation $\pi/4$ DQPSK

data rate up to 40 kb/s

COMP@N H09 Waveforms

BMS IP WF MANET class waveform mobile self-configuring and self-organizing network

extended range of services (retransmission within waveform – multihop relay)

operation in IP networks, build-in IP router, QoS supporting

W2FH EPM (Electronic Protective Measures) class waveform LPD (Low Probability of Detection)

LPI (Low Probability of Interception)

AJ (Anti-Jamming)

operating modes for BMS IP: 50 hop/s

for W2FH: 300 hop/s

simultaneous voice and data services

voice services digital voice (np. MELPe 2400, CODEC2)

group calls

privileged users

priority calls (break-in)

multi-hop voice

data services IP data

Serial data

SA (Situation Awareness) messages

GPS reports

short text messages

sensor data

files, video, pictures, mail transmission supporting

data retransmission

synchronization without GNSS (e.g. GPS)

channel for BMS IP: 50 kHz

for W2FH IP: 25 kHz

security (AES-256 based) TRANSEC

COMSEC

NETSEC

data rates BMS up to 40 kb/s

W2FH up to 3.3 kb/s

definable frequency range and sub-bands

pre-defined BMS IP WF or V2FH profiles with set of mission parameters (radio data, encryption keys)

operational in radio silence mode

number of networks 20



Mobile adapter with radio



Power amplifier



External loudspeaker



Handset

www.wbgroup.pl

RADMOR 
WB GROUP

The information in this folder is not intended to constitute an offer within the meaning of the Civil Code.

Copyright © 2023 RADMOR S.A. All rights reserved.

RADMOR S.A.
ul. Hutnicza 3, 81-212 Gdynia, Polska
t: +48 58 7655 621 | f: +48 58 7655 662
market@radmor.com.pl

QIV/2023